



Océ SCRMMO13 Laminated Scrim Vinyl Media

Laminated Matte Scrim Vinyl Solvent Inkjet Media



Product Description

A 13 oz. Laminated Scrim Vinyl Banner is engineered for UV Curable, solvent and eco-solvent printer technologies. This product provides outstanding image quality with superb dot control. The ideal product for general purpose banners when high tear resistance is required.

Canon
CANON GROUP

Specifications

Physical properties*

- Weight 13 oz/yd² or 440 gsm
- Yarn Denier 500D x 500D
- Threads 9 x 9
- Tensile Strength Weft 750 N/5cm, Warp 750 N/5cm
- Tear Strength Weft 180N, Warp 120N
- Peel Strength 40N/5cm
- Whiteness Point 87
- Gloss Level 8-15
- Flame Rating NFPA 701
- Temperature Resistance -30 to 70°C or 158°F
- Fungus Resistant Yes

* Target Values

Light Fastness

Light Fastness is a direct result of the ink used and the environment where the print is displayed. Please consult the ink manufacturer for light fastness data.

Features

- Matte finish
- Fast drying
- No Cadmium or lead fillers used
- Excellent image adhesion and durability

Recommended Storage Conditions and Shelf Life

- Store in clean, dry area away from direct sunlight
- Temperature 59-86F. (15-30 C.)
Relative Humidity 30-70%
- Repack opened rolls when not in use
- One year maximum at conditions noted above

Environmental, Health & Safety

- No Material Safety Data Sheet required
- Waste is not suitable for recycling

Main Applications

- Window displays
- Backdrops
- Construction site banners
- Trade show displays

Printer/ Ink Compatibility

Recommended for use in most solvent inkjet printers including: Océ® Low Solvent, Océ Eco-Solvent Ultra, Mimaki® ES3, SS2, SS2-1, HS, Hewlett-Packard® Eco-Sol, Roland® Eco-Sol Max, and Mutoh® Eco Solvent Ultra.

Handling Recommendations

Due to the absorptive nature of the coating, you should avoid touching the coated surface. It is always recommended that cotton gloves be worn when handling inkjet coated materials. Rolls are supplied coated side out.

Océ solvent and UV curable display graphics printing inkjet media supplies

Finishing Recommendations/Post Process

Pressure Sensitive vinyl laminates can be applied to increase the fade and abrasion resistance of the image. Polyester or other base material laminates are not recommended. Before applying the laminate, allow the image to dry for 24 hours. Residual solvent trapped beneath the laminate as a result of insufficient dry time can cause some color shifts.

Grommeting

Grommets should be placed in the hemline along the length of the banner so that the grommet is piercing through two layers. Corner grommets should be placed where the length and the width hems cross so that the grommet is through four layers. A reinforced corner is also recommended to increase durability.

Tape and Stitched Hem

Banner tape can be used and is preferred to sewing. If sewing, a double stitch hem is recommended with a maximum of five stitches per inch. Banner tapes at least 4 mils thick perform the best.

Selected available roll sizes

Item Number	Width x Length	Qty. per Carton	Core
SCRMMO1338	38" x 164'	1 roll	3"
SCRMMO1354	54" x 164'	1 roll	3"
SCRMMO1363	63" x 164'	1 roll	3"
SCRMMO1384	84" x 164'	1 roll	3"
SCRMMO1326	126" x 164'	1 roll	3"



©2011 Océ. Illustrations and specifications do not necessarily apply to products and services offered in each local market. Technical specifications are subject to change without prior notice. "Océ" and the Océ logo are registered trademarks of Océ-Technologies B.V. Corporation. All other product and company names are trademarks or registered trademarks and are the property of their owners and are respectfully acknowledged.



Printing for Professionals

Creating global leadership in printing

Canon and Océ join forces to create the global leader in the printing industry. For our customers this combines Canon and Océ technology with the support of the Océ direct sales and service organizations. Look to the new Canon-Océ combination for:

- Enterprise printing in the office and corporate printroom
- Large format printing of technical documentation, signage and display graphics
- Production printing for marketing service bureaus and graphic arts
- Business Services for document process outsourcing

Océ North America

Océ Imaging Supplies
1800 Bruning Drive West
Itasca, IL 60143-1093
To locate the name of your nearest Authorized Océ Media Dealer call:
1-800-323-4827
www.oceusa.com/imagingsupplies
email: us.info@oce.com

For information and services, visit us at:

www.oceusa.com